GSAS v3.8 Release Notes

GSAS Team February 10, 2004

Introduction

GSAS 3.8 contains fixes and minor modifications for L1A, Atmosphere, Waveform, and Elevation processes and products.

For L1A, the following changes were made:

- Improved GLA03 Quality Assurance Product (QAP).
- Added check to skip ancillary science packets if specific shot times = 0.
- Updated APID data structures to correspond with GLAS-582-SPEC-005-IPS45.xls
- Fixed errors and made general improvements in the GLA02 processing code, including using Pin E data for normalization of 532 laser energy data.
- Changed GLA02 transmit energy to 40/second.
- Fixed problem causing error when QAP04 was created.

For Waveforms, the following changes were made:

- Improved QAP05.
- Two parameters previously set invalid were redefined as spares

For Elevation processes, the following changes were made:

• Iceberg elevation parameter in GLA13 is now computed – it was previously set to invalid. This is computed blindly everywhere there are multiple peaks to the return, no sanity check is made to make sure it is not over land.

For Atmosphere, the following changes were made:

- Fixed beam_coelev and beam_azimuth on GLA08-11.
- Placed pad_angle on GLA08-11.
- Made major changes to the background computation.
- Improved layer threshold computations.

Other, more general fixes include:

- GLAS_Tick, a new PGE, was delivered to create oscillator rate trend files.
- Production documentation was updated/fixed.
- Significant changes were made to the QA and browse products.
- Metadata files were updated to work with ESDT changes.

Product Format/Definition Change Summary

GLA01:

minor modifications on engineering data descriptions update documentation for RecNRGLast_EU

GLA03:

Replaced existing spare55)i1b(8,4) with:

CD_PWaccum i4b(4)

CD_PWlong i1b(4)

CD_PWshort i1b(4)

CD_PWmsb i1b(4)

changed spare 55_4 i1b(8,4) to i1b(1,4)

GLA05:

spare1.1 (previous pcntsat1) chg to spare7

spare1.2 (previous pctnsat2) chg to spare8

GLA08-11:

Replaced existing spare, spare0 i1b(56) with:

PAD Angle pad_angle i4b(4)

changed spare spare0 i1b(56) to i1b(40)

The latest product formats/descriptions will be available at http://glas.wff.nasa.gov/v38_products/.

Known Problems

GLA16 still not supported.

Additional parameters need to be added to QAP03.

LRS subject change algorithm needs to be implemented.

SIRU sample time correction algorithm needs to be implemented.

More atmosphere changes are pending.

QAP05 lists all waveforms as always valid – this is a mistake- probably in the total number of waveforms

Lots of other QA tweaks needed.

Release Information

The ClearCase label for this release is RELEASE 3.8.

The release date is February 10, 2004.

Version numbers have been updated to "V3.8 February 2004" for the following:

- all libraries
- GLAS L1A
- GLAS Alt
- GLAS_Atm
- GLAS Meta
- anc07_02
- anc07_05
- anc45 01-15
- anc46 xx (see item 0001024)

This should be verified during operation by checking the version information in the appropriate ANC06 files.

SMDS Impact

The distribution tarfile is on glasdev.wff.nasa.gov at the following location:

```
/glasdev1/v3/dist/gsas_V3.8.tar.Z.
```

ANC Files

New versions of all the ANC07_02, ANC07_05, ANC45 and ANC46 data files are required.

New PGE

GLAS_Tick, a new PGE, is now provided. It should be run after the L1A process is completed and an ANC09 file is received. A new section has been added to the GSAS User Guide detailing the PGE.

Compilation

All libraries and binaries should be recompiled using the top-level Makefile.

IMPORTANT: due to internal changes in the makefiles, SDMS MUST use the command "make runtime" to ensure the software is made without debug flags.

The process for making the libraries and binaries is as follows (**NOTE: SDMS ONLY!!**)

```
cd /install_dir/gsas_v3.8
make runtime
make install
```

Note: developers should not use the above procedure. This procedure is for SDMS only!

Detailed Change Notes

0001264: maxiumum value of received energy needs to be higher change 20000 to 200000

GLA01_Main parameters i_RecNrgAll_EU and i_RecNrgLast_EU, max values have been changed from 2000 attojoules to 200000 attojoules in the product database documentation.

0001261: QABrowse problems

Fixed problem with case of the file extension on HDF output files. Fixed various problems seen in GSAS 3.8b2 ACCTEST products.

0001246: Bad APID19 record after MEU reset causes time problems

A new sanity check was introduced into GLAS_L0p which checks that the following shot counters are > 0 and < 200. The record is skipped if the test fails.

i_SCPosPktShot (Shot count for SC pos Pkt) shot(j)%i_ctr (Shot count)

0001243: Update Product Release Numbers in ANC45

The product release numbers were updated in ANC45 to Release 15.

00001218: Invalid Co-elevation angle on GLA10-11 and addition of pad_angle to GLA10-11

A software oversight was corrected which now allows the parameters beam_coelev and beam_azimuth to be propagated from GLA07 to products GLA08 through GLA11. In addition, software additions were made which place the pad_angle into products GLA08-GLA11. Online documentation has been modified to reflect this addition.

0001205: QAP04 caused EOF condition in some cases with ANC09

A single line of code got deleted out of L1A_QAP_mod.f90. This line initialized a variable which checked for the end of granule condition on QAP04. I have put this line back in.

0001204: ANC file ESDTs

Updated version numbers for the following ANC files:

GLAANC04 rel 5

GLAANC08 rel 5

GLAANC09 rel 9

GLAANC20 rel 4

GLAANC25 rel 5

GLAANC26 rel 1

GLAANC33 rel 7

GLAANC37 rel 3

GLAANC39 rel 4

0001193: Update GLA01 Documentation for i_RecNRGLast_EU

GLA01_Main variable i_recNRGLast_EU has been changed. Name Field and Description has been corrected to read per above instructions.

0001177: Normalization of 532 by Pin A in GLA02 problem

The change to the use of Pin E instead of Pin A for laser energy normalization in GLA02 will result in the removal of spurious signal intensity fluctuations introduced by the incorrect Pin A values. This will increase the quality of GLA07 and subsequent atm data products.

The background computation change should produce a more stable and reliable background subtraction that will increase the signal to noise of the daytime data.

The offsets applied to the range to the top of the profile (d_Rng2PCProf and d_Rng2CDProf) will increase the vertical alignment accuracy in GLA07. Prior versions of GLA07 had about a 2 bin (150 m) error in the vertical alignment of the data within the GLA07 height reference frame. This fix will also result in more accurate cloud and aerosol top and bottom (GLA08 and GLA09).

Additional changes made on cr1177:

L_Atm_mod.f90:

- major change made to background computation. A one second average background is computed from the average of the first 100 bins of the 20-40 km profile minus an assumed molecular backscatter contribution (a constant).
- Dead time correction change to 532 channel. New version first subtracts the background from received signal and dead time corrects the result.
- Valid raw data limits changed for 1064 channel. Prior versions required raw 1064 data to be >= 0 and <= 255. This was changed to >=-255 and <=500 to accommodate the fact that the droop correction will alter raw data values to this extent.

AtmMgr mod.f90:

• The biases applied to GLA02%d_Rng2PCProf and GLA02%d_Rng2CDProf had incorrect sign. Changed them to +206.8 and + 130.0, respectively.

A_20s_aer_det_mod.f90: (Actually done and merged from branch cr717 by mistake)

• Layer threshold computation changed to reduce occurrence of false positives.

A_4s_1064_det_mod:

• Layer threshold computation changed to increase effectiveness of finding layers.

A_pbl_det_mod: (Actually done and merged from branch cr717 by mistake)

• Added invalid data check.

A 20s 1064 det mod.f90:

• Layer threshold computation changed to reduce occurrence of false positives. Layer threshold computation changed to increase effectiveness of finding layers. Added invalid data check to fix IEEE overflow problem.

A_cld_lays_mod.f90, A_cld_det_mod.f90 and A_cld_grd_det_mod.f90:

• Changes to threshold computations to reduce false positives.

Anc07_0002.dat:

- Changed GI_AER_TOP_HT from 36000 to 30000. This is start height for aerosol layer searches.
- Changed GI_CC_ELIM_F from 1 to 0. This is the flag to eliminate calibration points taken during daylight. 1 eliminates them, 0 will include them.
- Changed GI_CALC_AER_F from 1 to 0. This flag determines which routine is used to find aerosol layers. 1 = use A_20s_aer_det; 0 = use A_cld_lays_mod

Const_atm_mod.f90:

• Changed gi_cal_ht_hi from 26000 to 23000. This is the height of the center of the high calibration band used for 532 calibration.

0001155: ANC09 data selector for GPS data

Created new PGE, GLAS_Tick, to create output files from ANC09/ANC32 and GLA03. The resulting outputs will be used for oscillator frequency monitoring. The User Guide has been updated with a new section for this PGE.

0001152: Change needed in QAP02 data structure

The GLA02 QAP files have been given an enhancement which provides more granularity in the energy distribution histograms.

0001122: QAP02 updates required to BROWSE software

Inspected new GLA02 QAP data and find it conforms to expectations from code changes made in Fortran which produces data for QAP. Plots are attached.

0001072: WF QA Needs To Be Updated

Updated QAP05 to include iQA100pLSat (percent of packet with low-gain saturation), iQA100pHSat (percent of packet with high-gain saturation), and iQA100pHFSat (percent of packet with high-gain sat+forward scattering) in the along track average, and i_pcntLSat (percent of granule with low-gain saturation), i_pcntHSat (percent of granule with high-gain saturation), and i_pcntHFSat (percent of granule with high-gain sat + forward scattering) in the QA summary record. Initialized all variables to invalid. Corrected problem in calculation of (WF centroid - centroid of max-amp peak).

Corrected QA code to gather skewness and kurtosis data only for WFs with one peak. Updated qapg code to include the new saturation flags. Changed min & max values for histograms of solution sigmas, standard deviation of fit, and (WF centroid - max-amp peak centroid).

0001071: GLA13 BergElev not set

Iceberg elevation parameter in GLA13 was previously not set in the code and had all default values. An initial algorithm has been implemented to compute this height. Although values are now available, they are very sparse. Fine-tuning of the algorithm is anticipated. NOTE: GLA13 includes some land. Iceberg elevation is still computed and reported wrongly for these land flagged data.

0001069: 532 Channel Background Computation

See 0001177.

0001068: GLA13 GLA02 QA tweaks

The QAP output for GLA02 has improved resolution for the energy histograms and a minor correction to the expected/processed counts.

0000960: Valid lat/lon produces invalid DEM elevation

The conditions cited by Jeff are only an explainable anomaly and do not constitute an error. Elevations runs show that the interval in question occurs over a coordinate range of roughly -77.7 lat / 184.6 lon through -82.8 lat / 169.0 lon. The DEM elevations are indeed invalid as reported; however, the entire interval occurs over the Ross Ice Shelf. At the end of the interval the DEM elevations become vaild, as expected over the true Antarctic land mass. The etopo30 DEM used as of this entry records an ice shelf as being over ocean, and not land. There is no software or data error.

0000952: pcntsat1, i pcntsat2 Should Be Changed To Spares

Changed _pcntSat1 & _pcntSat2 to _spare7 & _spare8. Changes to qapg (to display saturation data from wfQual) should be done on another branch.

GLA05%i_pcntsat1 and GLA05%i_pcntsat2 have been changed to GLA05%i_spare7 and GLA05%i_spare8. The online documentation was updated by Dennis and confirmed by LeeAnne Roberts. Code changes confirmed by Steve McLaughlin.

0000943: GLA01 engineering data needs to define values

Added the following comments in the description:

```
d_engineering(1) = active detector temperature [T_detID
    if detector=1, T_detID = GLA00_prod%CTHW3_hk(1)%i_PRTad1C24_t
    if detector=2, T_detID = GLA00_prod%CTHW3_hk(1)%i_PRTad2C25_t]
d_engineering(2) = active digitizer temperature [T_digID
    if digitizer=1, T_digID = GLA00_prod%CTHW3_hk(1)%i_AD1ADCC19_t
```

```
if digitizer=2, T_digID = GLA00_prod%CTHW3_hk(1)%i_AD2ADCC20_t]
d_engineering(3) = oscillator board temperature
    [T_relay = GLA00_prod%CTHW3_hk(1)%i_OscBdC11_t]
d_engineering(4) = Fiber Box temperature
    [T_fb = GLA00_prod%CTHW3_hk(1)%i_PRTfboxC29_t]
d_engineering(5) thru d_engineering(12) TBD. All temperatures are in Celsius X 100.
```

0000903: GLAS 532 nm PBL and Aerosol Layer Heights (GLA08)

See 0001177

0000902: GLAS 532 nm Cloud Layer Heights (GLA09)

Changes to threshold computations to reduce false positives were made in the following files: A_cld_lays_mod.f90, A_cld_det_mod.f90 and A_cld_grd_det_mod.f90:

0000779: WFMgr on integration branch crashes with out of bounds error

When I ran this using LeeAnne's setup, the error did not occur. Thus, this appears to be due to an error in the configuration file. Can't reproduce the problem.

0000752: GLAS telemetry changes

```
GLA00 changes detected are as follows (APID55 only):

<integer (kind=i1b) :: i_spare50_4(8) !Spare in telemetry
---

> integer (kind=i4b) :: iCD_PWaccum !CD PW Limit Violation counter

> integer (kind=i1b) :: iCD_PWlong !CD Long PW Violation counter

> integer (kind=i1b) :: iCD_PWshort !CD Short PW Violation counter

> integer (kind=i1b) :: iCD_PWmsb !CD Short PW MSB

> integer (kind=i1b) :: i_spare50_4(1) !Spare in telemetry

Made documentation changes to the Product Database for GLA03. The changes are: integer (kind=i1b) :: i_spare55_4 (8,4)<---replace
integer (kind=i4b) :: iCD_PWaccum (4)<---New addition
integer (kind=i1b) :: iCD_PWshort (4)<---New addition
integer (kind=i1b) :: iCD_PWmsb (4)<---New addition
integer (kind=i1b) :: iCD_PWmsb (4)<---New addition
integer (kind=i1b) :: iSpare55_4 (1,4)<---changed size
```

0000717: GLAS_Atm is generating an IEEE overflow for certain data

The IEEE overflow was traced to a line of code in A_20s_1064_det_mod.f90 that computed the average and standard deviation of a few km of atmospheric profile. If all the bins in this few km were invalid, the std deviation was calculted as invalid. The std deviation was then used to compute a threshold and this would cause the overflow. A check on the magnitude of the std deviation was added to catch this condition.

0000673: running without pad and pod in for elevation mgr gives different results

Running elevations without the PAD and POD now provides effectively the same results as running with them, provided that the PAD and POD are the same ones used when generating the original GLA05 with waveforms software.

0000665: L1A Transmit energy per shot

Modified L1A to calculate transmitted energy (for GLA02) at 40Hz instead of repeating the value for shot 1 forty times.

0000611: GLA05 QA problems in Release 11+

Updated QAP05 to include iQA100pLSat (percent of packet with low-gain saturation), iQA100pHSat (percent of packet with high-gain saturation), and iQA100pHFSat (percent of packet with high-gain sat+forward scattering) in the along track average, and i_pcntLSat (percent of granule with low-gain saturation), i_pcntHSat (percent of granule with high-gain saturation), and i_pcntHFSat (percent of

granule with high-gain sat + forward scattering) in the QA summary record. Initialized all variables to invalid. Corrected problem in calculation of (WF centroid - centroid of maxamp peak). Corrected QA code to gather skewness and kurtosis data only for WFs

with one peak. Updated qapg code to include the new saturation flags. Changed min & max values for histograms of solution sigmas, standard deviation of fit, and (WF centroid - max-amp peak centroid).

0000601: Unexpected latitudes in GLA12-15 along-track records

This problem is apparently resolved on the integration branch. For a GLA12 qap file generated on the main branch only,

IDL> data=qapread('/home/jack/GLA12_012_1102_002_0021_0_01_main_0001.qap')

IDL> print,min(abs(data.alongtrack.dqa100lat))

37.384362

whereas the same run using code from integration gives

IDL> data=qapread('/home/jack/GLA12_012_1102_002_0021_0_01_integ_0001.qap')

IDL> print,min(abs(data.alongtrack.dqa100lat))

69.044922

It is not clear which change fixed this problem. None of the ones listed in the history for elevmgr_mod.f90 since the last change on main address it directly.

0000518: Inconsistent/incorrect determination of end of QAP averaging period: GLA05

The production of the GLA05 QAP file was amended so that it utilizes standard timing software employed for other GLA QAP products.

0000501: GLA01 QA averages include bad data

GLA01 QAP data has been updated to remove statistics based on spurious additions from invalid records, thus improving the accuracy and validity of the QA data available.

0000430: Global avg std dev set to invalid if all values of parameter are the same

A/D receiver gain statistics are now available in the GLA01 QAP file.

Changed ANC07 Parameters:

```
changed GI_AER_TOP_HT from 36000 to 30000
changed GI_CALC_AER_F from 1 to 0
changed GI_CC_ELIM_F from 1 to 0

ANC07_05
changed GI_G_USEDBG from 2 to 1
changed GD_IR_MAXLID from 255 to 500
Added D_QA_G_NRG_HIST and D_QA_IR_NRG_HIST
Removed D_QA_NRG_HIST
```

Changed Files:

```
./data/anc07_001_01_0002.dat
./data/anc07_001_01_0005.dat
./data/anc45_001_01_0001.dat
./data/anc45_001_01_0002.dat
./data/anc45_001_01_0003.dat
./data/anc45_001_01_0004.dat
./data/anc45_001_01_0005.dat
./data/anc45_001_01_0006.dat
./data/anc45_001_01_0007.dat
```

```
./data/anc45_001_01_0008.dat
```

./idl/qa_browse/browse/qab_gndtrkmap.pro

./idl/qa_browse/browse/qab_outputfilename.pro

./idl/qa_browse/browse/qab02.pro

./idl/qa_browse/browse/qab02_lowerlevelplots.pro

./idl/qa_browse/browse/qab02_upperlevelplot.pro

./idl/qa_browse/browse/qab05.pro

./idl/qa_browse/browse/qab05_gndtrkmapclose.pro

./idl/qa_browse/browse/qab05_groundtrackmaps.pro

./idl/qa_browse/browse/qab05_histograms.pro

./idl/qa_browse/browse/qab05_lowerlevelplots.pro

./idl/qa_browse/browse/qab05_plottable.pro

./idl/qa_browse/browse/qab05_upperlevelplot.pro

./idl/qa_browse/browse/qab05_writetabletoplot.pro

./idl/qa_browse/browse/qab13and15_upperlevelplot.pro

./idl/qa browse/browse/qabrowse.pro

```
./idl/qa_browse/compare/qapcompare.pro
./idl/qa_browse/read/qapread.pro
./idl/qa_browse/util
./idl/qa_browse/util/hdf2png.pro
./idl/qa_browse/util/qab_translatecomponentstatus.pro
./idl/qa_browse/util/qap02V2_datastruct.pro
./idl/qa_browse/util/qap05_datastruct.pro
./idl/qa_browse/util/qap05V2_datastruct.pro
./idl/qa_browse/util/strprint.pro
./idl/qa_browse/util/tvread2.pro
./Makefile
./src
./src/atm_lib/vers_atm_mod.f90
./src/atmosphere/common/A_buff_data_mod.f90
./src/atmosphere/layers/A_20s_1064_det_mod.f90
./src/atmosphere/layers/A_20s_aer_det_mod.f90
./src/atmosphere/layers/A 4s 1064 det mod.f90
./src/atmosphere/layers/A_cld_det_mod.f90
./src/atmosphere/layers/A_cld_grd_det_mod.f90
./src/atmosphere/layers/A_cld_lays_mod.f90
./src/atmosphere/layers/A_pbl_det_mod.f90
./src/atmosphere/layers/A_pbl_lay_mod.f90
./src/atmosphere/opt_props/A_cld_opt_prop_mod.f90
./src/common_libs/anc_lib/anc07_11a_mod.f90
./src/common_libs/anc_lib/anc32_gps_mod.f90
./src/common_libs/anc_lib/vers_anc_mod.f90
./src/common_libs/cntrl_lib/vers_cntrl_mod.f90
./src/common_libs/err_lib/vers_err_mod.f90
./src/common libs/exec lib/fCntl mod.f90
./src/common_libs/exec_lib/get_fileindex_mod.f90
./src/common_libs/exec_lib/vers_exec_mod.f90
./src/common libs/file lib/vers file mod.f90
```

```
./src/common_libs/geo_lib/vers_geo_mod.f90
./src/common_libs/Makefile
./src/common_libs/math_lib/c_minmaxmean_mod.f90
./src/common libs/math lib/vers math mod.f90
./src/common_libs/platform_lib/const_atm_mod.f90
./src/common libs/platform lib/const glob mod.f90
./src/common_libs/platform_lib/const_l1a_mod.f90
./src/common_libs/platform_lib/vers_platform_mod.f90
./src/common_libs/prod_lib/GLA00_alg_mod.f90
./src/common_libs/prod_lib/GLA00_mod.f90
./src/common_libs/prod_lib/GLA00_prod_mod.f90
./src/common_libs/prod_lib/GLA00_scal_mod.f90
./src/common_libs/prod_lib/GLA02_Pass_mod.f90
./src/common_libs/prod_lib/GLA03_alg_mod.f90
./src/common_libs/prod_lib/GLA03_print_mod.f90
./src/common_libs/prod_lib/GLA03_prod_mod.f90
./src/common libs/prod lib/GLA03 scal mod.f90
./src/common_libs/prod_lib/GLA05_alg_mod.f90
./src/common_libs/prod_lib/GLA05_print_mod.f90
./src/common_libs/prod_lib/GLA05_prod_mod.f90
./src/common_libs/prod_lib/GLA05_scal_mod.f90
./src/common_libs/prod_lib/GLA07_alg_mod.f90
./src/common_libs/prod_lib/GLA07_prod_mod.f90
./src/common_libs/prod_lib/GLA07_scal_mod.f90
./src/common_libs/prod_lib/GLA08_alg_mod.f90
./src/common_libs/prod_lib/GLA08_prod_mod.f90
./src/common_libs/prod_lib/GLA08_scal_mod.f90
./src/common_libs/prod_lib/GLA09_alg_mod.f90
./src/common libs/prod lib/GLA09 prod mod.f90
./src/common_libs/prod_lib/GLA09_scal_mod.f90
./src/common_libs/prod_lib/GLA10_alg_mod.f90
./src/common libs/prod lib/GLA10 prod mod.f90
```

```
./src/common_libs/prod_lib/GLA10_scal_mod.f90
./src/common_libs/prod_lib/GLA11_alg_mod.f90
./src/common_libs/prod_lib/GLA11_prod_mod.f90
./src/common_libs/prod_lib/GLA11_scal_mod.f90
./src/common_libs/prod_lib/vers_prod_mod.f90
./src/common_libs/time_lib/vers_time_mod.f90
./src/create_dem
./src/dem2vis
./src/elev lib
./src/elevations
./src/elevations/anc09_pad_mod.f90
./src/glas_alt/ElevMgr_mod.f90
./src/glas_alt/GLAS_Alt.f90
./src/glas_alt/WFMgr_mod.f90
./src/glas_apid/GLAS_APID.f90
./src/glas_atm/AtmMgr_mod.f90
./src/glas_atm/GLAS_Atm.f90
./src/glas_10p/GLAS_L0proc.f90
./src/glas_l0p/glop_mod.f90
./src/glas_l1a/GLAS_L1A.f90
./src/glas_11a/L1A_QAP_mod.f90
./src/glas_meta/GLAS_Meta.f90
./src/glas_reader/GLAS_Reader.f90
./src/glas_tick/eCntl_mod.f90
./src/glas_tick/GetControl_mod.f90
./src/glas_tick/GLAS_Tick.f90
./src/glas_tick/Makefile
./src/glas_tick/ReadTickData_mod.f90
./src/glas_tick/TickGranule_mod.f90
./src/glas_tick/TickHdr_mod.f90
./src/glas_tick/TickStats_mod.f90
./src/l1a_lib/L_Alt_mod.f90
```

```
./src/l1a_lib/L_Atm_mod.f90
./src/l1a_lib/L_Eng_mod.f90
./src/l1a_lib/QAP01_mod.f90
./src/l1a_lib/QAP02_mod.f90
./src/l1a_lib/vers_l1a_mod.f90
./src/Makefile
./src/prod_util/product_test/gla05_minmax_mod.f90
./src/prod_util/scantime/scantime.f90
./src/qapg/qapg_gla05_at.f90
./src/qapg/qapg_gla05_sum.f90
./src/qapg/qapg_gla05_sum.f90
./src/reforbit_util/c_procRefOrbit_mod.f90
./src/waveforms/W_Assess/W_Assess_mod.f90
./src/waveforms/W_Common/QA_wf_mod.f90
```

./src/waveforms/W_Common/W_Types_mod.f90

./src/waveforms/W_CreQAStats/W_CreQAStats_mod.f90

./src/waveforms/W_FunctionalFt/W_FunctionalFt_mod.f90